



Pro Mix[®] Industry



What PMI Top Coat to Use?



AK-232-XX (30 and 90)

Fast Dry Enamel - Mainly used for Engineering

Type applications, Brackets, Welding Repairs etc.

Anything that requires a Fast Drying 1k Product.

Use on Steel. Can be DTM but ideally use a

Primer Underneath



AK-240-90

Spraying Enamel— Mainly used for Agricultural and Engineering Projects. Tractors, Diggers, Excavators, Trailers etc. Use on Steel. Can be DTM but ideally use a Primer Underneath





Pro Mix® Industry





PU 240-90

High Quality Polyurethane Topcoat

Used for all 2k Top Coating. Very durable

And easy to spray. Recommend to use a Primer

underneath. This is the **Go To** 2k Top Coat in PMI for

High Quality Results



PU 250- XX (30,50 and 90)

High Quality PU DTM Top Coat

Mainly used for Industrial and Agricultural applications. Will grip onto those hard to reach places of Machinery etc.

Available in Matt, Satin and Gloss. Also used for Floor Coatings @ 8:1. If Top Coating Truck Cabs etc. use PU240-90 instead for harder wearing.





Pro Mix[®] Industry





AY 210-90

ACRYLIC 1K TOP COAT

Fast Drying Acrylic Top Coat. Recoatable in 15 min
Mainly used on Vehicles, Industrial Parts, Signs,
Machines etc. Can be used in Aerosols. Excellent Gloss

If you are not sure contact the following

Kerry Clark 027 230 0057

Mark Floris 027 241 1014





Pro Mix® Industry



What PMI Primer to Use?



EP 100-20

EPOXY PRIMER - Full Epoxy Primer. Can be Tinted to any colour. Awesome Corrosion Protection. Goes over all metals. Top Coat after 1 hr @20°c.

Great to use under poor covering colours. Can be Top Coated up to 14 Days without Sanding.



EA 100-20

Primer. Can be Tinted to any colour. Awesome Corrosion Protection. Goes over all metals. Top Coat after 20min @20°c . Fast process for Aluminum Boats. Can be Top Coated up to 4 weeks without sanding.

EPOXY ACRYLIC PRIMER - Epoxy Acrylic





Pro Mix[®] Industry





AY 100-20

1K ACRYLIC PRIMER— Excellent adhesion to Steel and Zinced substrates. Good adhesion to Aluminum. Available in Grey and Black. Has Zinc Phosphate. Excellent filling properties and short drying times. Topcoat after 1 hr @ 20°c

If you are not sure contact the following

Kerry Clark 027 230 0057

Mark Floris 027 241 1014