DuoCryl Härter

Technical Information

Characteristics:	**R**eactant based on polyisocyanate for DD- or. PU paints. A perfect result can only be achieved by carrying out the following instructions.
Area of application:	**H**ardener for **DuoCryl-** and **RoCryl-products.**
Mixing ratio:	Observe the mixing ratio mentioned on the paint container.
Special remarks:	The hardener is moisture sensitive and a reaction with air humidity renders the hardener unusable. Therefore close the can tightly immediately after every withdrawal.
Cleaning of tools:	**Waschlöser Nr. 52** and **PUG P**insel- **u**. **G**erätereiniger.
Storage:	At least 2 years in unopened original container. Frequent opening and partial withdrawal may cause a rise of viscosity.
Please consider:	The product and the recommendations in this technical data sheet correspond to today's state of the art. Our oral and written application recommendations, that are based on years of experience and provided to the best of knowledge, are non-committal and do not establish a contractual relationship and secondary obligation of the sales contract. They do not release the user from his obligation to verify on his own responsibility the existing substrate and the suitability of our products for the intended purpose. In case of doubt, suitability and spreading rate are to be tested by creating a sample. If our products are combined or intermixed with third-party products we cannot guarantee a perfect surface finish. Our general terms and conditions apply.

This technical data sheet replaces all previous versions.

Edited 09/17

A trademark of
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach

Tel.: +49 8703 92 20
Fax: +49 8703 92 21 00

E-Mail: info@rosner-coatings.com
www.rosner-coatings.com